TIMPTE® SUPER HOPPER



www.TIMPTE.com

TUB OPTIONS

AG HOPPER 25"



Design: Two piece formed tub Aluminum: .125" Side Slope: 35.8 Degrees Ground Clearance: 25"

HI-FLOW 20.5"



Design: Two piece formed tub Aluminum: .125" Side Slope: 43.5 Degrees Ground Clearance: 20.5"

SPLIT TUB



Design: Two piece formed tub Aluminum: .125" Side Slope: 43.5 Degrees Ground Clearance: 17" *Riveted Split Tub with .080" and .100" aluminum - standard for all 102" wide trailers and 96" wide 43' - 50'

Removable Vibrators

Two-Speed Operator



Permanent Vibrators



Double Knock Rails Full Double Knock Rails



Interior Access Steps

PANEL OPTIONS & SIDEWALL HEIGHTS





Other Colors: Available Upon Request

Tub Option

Since 1884

AVAILABLE

SIDEWALL HEIGHTS



POWER OPTIONS

One-Touch™ Technology allows the operator to open and close the tarp system with one push of a button

One-Touch™ Technology works by measuring amperage load to a preset value

Start, stop, and reverse your tarp direction with one push of a button

Simple 3-button remote design is easy to operate, with large easy-to-read buttons

This powerful remote can operate up to 5 different trailer accessories with a maximum range of 100 ft. • Tarp • Front Hopper • Rear Hopper • 3rd Hopper • Work Lights • etc.

Optional Manual Override System



TAKE CONTROL WITH ONE REMOTE



Features:

Industries BEST Swing Clearance; No trap operator or motor to interfere with swing auger Operates using a single 12 volt

close the tarp system with one push

of a button - Patent Pending -

Control box protects all electrical components from corrosion and road debris

Moisture-Resistant Control Box

- hydraulic motor
- No Limit Switches
 - Easily control product flow by feathering the door open or close Hydraulic motor and reservoir are protected in the apex of the trailer

OPTIONS



AXIES & BRAKES Disk Brakes

































